Torro Plus





Application:
Upholstery fabric suitable for soft and restaurant style seating
Composition:
54.2% Polyurethane, 26.3% Polyester, 19.5% Cotton
Width:
137 cms + 2% usable
Weight:
560 gms/m2 (includes FR back coating)
Abrasion:
BS EN ISO 5470 - 2 : 2003 Method 1 > 100,000 Rubs
Flexing:

Flame Retardancy:
BS EN 1021 – 1: 2006 (Cigarette)
BS EN 1021 – 2: 2006 (Match)
BS 7176: 2007 Low Hazard
BS 7176: 2007 Medium Hazard
BS 5852: Section 4 Ignition Source 5
Note: FR back coating applied to achieve FR levels
Note: Flammability performance is dependent on foam used.
Tensile Strength:

BS EN ISO 13934-1: 1999

Tear Resistance:
BS EN ISO 13927-2 : 2000
Torn across length 46N, Torn across width 47N
Light Fastness:
BS EN ISO 105 – BO2 : Method 3 to Standard – 5
Sea Water Fastness:
BS EN ISO 105 – E02: 1996 - 5
Fastness to Rubbing Wet & Dry:
BS EN ISO 105 – X12 : 2002 – 5
Colour Matching:

Batch to batch variations in shade may occur within commercial tolerances. We recommend that fabric be examined before use as no claims

Lengthway 640N, Widthway 470N

will be considered after cutting.

Availability:
Generally ex stock
Product Development:
We reserve the right to change the specification of our products in line with our product development program without notice.
Fabric Care andMaintenance:
Remove any spillages or stains with a damp cloth. Please refer to our cleaning and maintenance guide for additional details.
TechnicalAssistance:
Our Technical staff will be pleased to offer advice on F.R. and all other technical matters.